

SAFETY DATA SHEET

1. Identification

Label elements

Product identifier	A&L Cosmoline Remover	
Other means of identification		
Product Code	1168	
Recommended use	Cosmoline Remover	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/I	Distributor information	
Manufacturer		
Company name	Malco Products, Inc.	
Address	361 Fairview Ave	
	Barberton, OH 44203	
	United States	
Telephone	Phone	800-253-2526
	Fax	330-753-2025
Website	www.malcopro.com	
E-mail	msdsinfo@malcopro.com	
Contact person	Technical Department	
Emergency phone number	Phone 1-800-424-9300	
2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 5

-	•	• •
Health hazards	Acute toxicity, oral	Category 5
	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Signal word Danger Highly flammable liquid and vapor. May be harmful if swallowed. May be fatal if swallowed and **Hazard statement** enters airways. Harmful in contact with skin. Causes skin irritation. Harmful if inhaled. **Precautionary statement** Prevention Keep away from heat/sparks/open flames/hot surfaces, - No smoking, Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing. Wear protective gloves/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all Response contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	56.98% of the mixture consists of component(s) of unknown acute dermal toxicity. 56.98% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Solvent Naphtha (Petroleum), Light Aliph.		64742-89-8	50 - < 60
Xylene		1330-20-7	30 - < 40
Ethylbenzene		100-41-4	5 - < 10
Other components below reportable le	evels		< 1

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell. Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause Most important temporary irritation. Skin irritation. May cause redness and pain. symptoms/effects, acute and delaved Indication of immediate Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water medical attention and special immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under treatment needed observation. Symptoms may be delayed. Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the **General information** material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. 5. Fire-fighting measures Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media Specific hazards arising from Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become the chemical electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

and precautions for firefighters Fire fighting In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do equipment/instructions so without risk. Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards

Special protective equipment

6. Accidental release measures

	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
	for later disposal. Clean surface thoroughly to remove residual contamination.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to
·	avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash contaminated clothing before reuse.
	Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National
	2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National
including any incompatibilities	 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code". Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
	 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code". Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Components	Туре	Value	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	

Components	Ту	pe	Va	alue
Ethylbenzene (CAS 100-41-4)	ΤV	VA	20) ppm
Xylene (CAS 1330-20-7)	ST	EL	15	i0 ppm
	TV	VA	10	10 ppm
US. NIOSH: Pocket Guide		-		
Components	Ту	pe	Va	alue
Ethylbenzene (CAS 100-41-4)	ST	EL		5 mg/m3
	TV	VA		25 ppm 15 mg/m3
	IV	VA		io ng/mo i0 ppm
ological limit values				- FF
ACGIH Biological Exposi Components	ure Indices Value	Determinant	Specimen	Sampling Time
			•	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid	Creatinine in urine	*
		and		
		phenylglyoxyli acid	С	
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric	creatinine in	*
,	00	acids	urine	
* - For sampling details, ple	ease see the source d	ocument.		
lividual protection measure	established, mair shower must be es, such as personal	ntain airborne level available when han protective equipr	s to an acceptable dling this product. nent	e limits. If exposure limits have not been level. Eye wash facilities and emergency
Eye/face protection	Face shield is re	commended. Wear	safety glasses with	h side shields (or goggles).
Skin protection				
Hand protection	Wear appropriate	e chemical resistan	t gloves.	
Other	Wear appropriate	e chemical resistan	t clothing. Use of a	n impervious apron is recommended.
Respiratory protection	limits (where app		ceptable level (in c	ntrations below recommended exposure ountries where exposure limits have not rn.
Thermal hazards	Wear appropriate	e thermal protective	clothing, when ne	cessary.
neral hygiene nsiderations	hygiene measure	es, such as washing	g after handling the	drink. Always observe good personal material and before eating, drinking, and equipment to remove contaminants.
Physical and chemica	al properties			
pearance	Clear.			
Physical state	Liquid.			
Form	Liquid.			
Color	Colorless			
lor	Xylene			
lor threshold	Not available.			
	None			
Iting point/freezing point	-138.82 °F (-94.9	°C) estimated		
- J				

250.41 °F (121.34 °C) estimated Initial boiling point and boiling range 60.0 °F (15.6 °C) Flash point

Evaporation rate

Material name: A&L Cosmoline Remover

1168 Version #: 03 Revision date: 03-27-2015 Issue date: 10-01-2014

Not available.

Flammability (solid, gas)	Not available.		
Upper/lower flammability or exp			
Flammability limit - upper (%)	6.8 % estimated		
Explosive limit - lower (%)	Not available.		
Explosive limit - upper (%)	Not available.		
Vapor pressure	Not available.		
Vapor density	Not available.		
Relative density	Not available.		
Solubility(ies)			
Solubility (water)	Not available.		
Partition coefficient (n-octanol/water)	Not available.		
Auto-ignition temperature	810 °F (432.22 °C) estimated		
Decomposition temperature	Not available.		
Viscosity	Not available.		
Other information			
Density	6.71 lb/gal		
Flammability class	Flammable IB estimated		
Kinematic viscosity	6.21 cSt		
Kinematic viscosity temperature	68 °F (20 °C)		
VOC (Weight %)	100 % by weight		
10. Stability and reactivity			
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.	
Skin contact	Harmful in contact with skin. Causes skin irritation.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	May be harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain.	

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Harmful if inhaled. Harmful in contact with skin.	
Components	Species Test Results	
Ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	17800 mg/kg

Components	Species	Test Results		
Oral				
LD50	Rat 3500 mg/kg			
Xylene (CAS 1330-20-7)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 43 g/kg		
Inhalation				
LC50	Mouse	3907 mg/l, 6 Hours		
	Rat	6350 mg/l, 4 Hours		
Oral				
LD50	Mouse	1590 mg/kg		
	Rat	3523 - 8600 mg/kg		
* Estimates for product may b	be based on additional compone	nt data not shown.		
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Direct contact with eyes may	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not available.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.			
IARC Monographs. Overall	Evaluation of Carcinogenicity			
Ethylbenzene (CAS 100- Xylene (CAS 1330-20-7) OSHA Specifically Regulate Not listed.		2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans. 001-1050)		
Reproductive toxicity	Components in this product h laboratory animals.	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.		
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	May be fatal if swallowed and	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inhalation may be	armful. Prolonged exposure may cause chronic effects.		
12. Ecological information	ı			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			

Components		Species	Test Results
Ethylbenzene (CAS 10)0-41-4)	-	
Aquatic	,		
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Xylene (CAS 1330-20-	-7)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.

Partition coefficient n-oc	ctanol / water (log Kow)	
Ethylbenzene	3.15	
Xylene	3.12 - 3.2	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN number	UN1993
UN proper shipping name	Flammable Liquid, N.O.S (Naptha and Xylene)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1993
UN proper shipping name	Flammable Liquid, N.O.S (Naptha and Xylene)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
IMDG	
UN number	UN1993
UN proper shipping name	Flammable Liquid, N.O.S (Naptha and Xylene)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, <u>S-E</u>
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

DOT



15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US federal regulations

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylbenzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.
SARA 304 Emergency release notification	

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
SARA 302 Extremely hazaro Not listed.	dous substance
SARA 311/312 Hazardous chemical	No
SARA 313 (TRI reporting)	

Chemical name CAS number % by wt. Xylene 1330-20-7 30 - < 40</td> Ethylbenzene 100-41-4 5 - < 10</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4) Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) US state regulations US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed. US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) Ethylbenzene (CAS 100-41-4) Solvent Naphtha (Petroleum), Light Aliph. (CAS 64742-89-8) Xylene (CAS 1330-20-7) **US. Massachusetts RTK - Substance List** Ethylbenzene (CAS 100-41-4) Xylene (CAS 1330-20-7) US. New Jersey Worker and Community Right-to-Know Act Ethylbenzene (CAS 100-41-4) Xylene (CAS 1330-20-7) US. Pennsylvania Worker and Community Right-to-Know Law Ethylbenzene (CAS 100-41-4) Xylene (CAS 1330-20-7) US. Rhode Island RTK Ethylbenzene (CAS 100-41-4) Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-01-2014
Revision date	03-27-2015
Version #	03

Disclaimer Malco Automotive cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This document has undergone significant changes and should be reviewed in its entirety.

Revision Information