

# SAFETY DATA SHEET

**Revision Date:** 08-27-2015

Version 1

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code(s): Product Name 21342000-M RUST VETO 342

Recommended use Uses advised against Rust preventive Any other purpose.

#### Manufacturer, Importer, Supplier

Houghton International Inc. Madison & Van Buren Aves. Valley Forge, PA 19482 Telephone: 610-666-4000 FAX: 610-666-1376 Website: www.houghtonintl.com Customer Service: 888-459-9844 Houghton Canada 915 Meyerside Drive Mississauga ON LST 1R8

#### Emergency telephone number

3E Company 1-866-519-4752 (USA, Canada, Mexico) Company Access Code: 333938

# **SECTION 2: HAZARDS IDENTIFICATION**

#### **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

#### GHS Label elements, including precautionary statements

Signal Word Warning

#### Hazard Statements

Causes serious eye irritation May cause drowsiness or dizziness Flammable liquid and vapor



#### **Precautionary Statements**

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/ .? /equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection Keep cool **Precautionary Statements - Response** 

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage** 

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

#### Other information

Not applicable

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

This product is a mixture. Health hazard information is based on its ingredients.

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated light	64742-47-8	25% - 60%
Calcium dihydroxide	1305-62-0	1% - 2.5%
2-Methylpentane-2,4-diol	107-41-5	1% - 2.5%

#### Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

# **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first-aid measures

General advice	Do not get in eyes, on skin, or on clothing. When symptoms persist or in all cases of doubt seek medical advice. Do not breathe dust/fume/gas/mist/vapors/spray.
Inhalation	Move to fresh air. If symptoms persist, call a physician.

Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. If symptoms persist, call a physician.	
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.	
4.2. Most important symptoms and	and effects, both acute and delayed	
Main Symptoms	Eye damage/irritation	
4.3. Indication of immediate medical attention and special treatment needed		
Notes to physician	Treat symptomatically.	

# **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

#### Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

#### 5.2. Special hazards arising from the substance or mixture

#### Special Hazard

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Flammable. Risk of ignition. Thermal decomposition can lead to release of irritating gases and vapors.

#### **Hazardous Decomposition Products**

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

## 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Keep people away from and upwind of spill/leak.

Advice for non-emergency Eliminate all ignition sources if safe to do so. Evacuate personnel to safe areas.

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and materials for containment and cleaning up

After cleaning, flush away traces with water.

#### 6.4. Reference to other sections

See Section 8/12/13 for additional information

# **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Advice on safe handling. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children.

#### Recommended Shelf Life

No information available.

#### Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

#### 7.3. Specific end uses

Specific use(s)

Rust preventive

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	AIHA WEEL
Calcium dihydroxide 1305-62-0	TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup> total dust		TWA: 5 mg/m <sup>3</sup>	
1303-02-0		TWA: 5 mg/m <sup>3</sup> respirable fraction		
		(vacated) TWA: 5 mg/m <sup>3</sup>		
		not in effect as a result of		
		reconsideration		
2-Methylpentane-2,4-diol	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm	Ceiling: 25 ppm Ceiling: 125	
107-41-5		(vacated) Ceiling: 125 mg/m <sup>3</sup>	mg/m³	

**Other Exposure Guidelines** 

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls** 

#### **Engineering Measures**

Showers

Eyewash stations Ventilation systems.

#### Individual protection measures, such as personal protective equipment

Eye/Face Protection	Tightly fitting safety goggles.
Skin and body protection	Wear protective gloves/clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical state @20°C Odor	liquid mineral oil	Appearance Odor Threshold	light brown Not Applicable
Property pH	<u>Values</u> No information availa	hle	Note
Melting Point / Freezing Point	t No information availa	able	
Boiling point/boiling range	No information availa	able	
Flash point Evaporation rate	41 °C / 106 °F < 1		Tag closed cup (BuAc = 1)
Flammability (solid, gas)	No information availa	able	(Burd=1)
Flammability Limits in Air			
upper flammability limit	No information availa	ble	
Lower flammability limit	No information availa	ble	
Vapor pressure	No information availa	blo	
Vapor pressure Vapor density	No information availa		
Relative density	0.87		g/cm3 @15.5°C
Solubility(ies)	negligible		grania e la a
Partition coefficient: n-octand	00		
Autoignition temperature	No information availa	ble	
Decomposition temperature	No information availa	able	
Viscosity, kinematic	85 cSt @ 40 °C		
Explosive properties	Not Applicable		
Oxidizing Properties	Not Applicable		
9.2 Other information			
Viscosity, kinematic (100°C)	No information availa		
Pour point	No information availa	able	
VOC Content (ASTM E-1868-1 VOC Content	<li>10) ~ 402 g/L No information availated and the second second</li>	able	ASTM E1868-10

# SECTION 10: STABILITY AND REACTIVITY

## 10.1. Reactivity

None under normal use conditions

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

None under normal use conditions

#### 10.4. Conditions to avoid

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity, Keep away from open flames, hot surfaces and sources of ignition

#### 10.5. Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

roduct Information There is no data available for this produce	
Inhalation	Vapors may cause drowsiness and dizziness.
Eye contact	Irritating to eyes.
Skin contact	There is no data available for this product.
Ingestion	There is no data available for this product.

#### **Component Information**

Pr

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Calcium dihydroxide 1305-62-0	7340 mg/kg(Rat)		
2-Methylpentane-2,4-diol 107-41-5	3692 mg/kg(Rat)	= 8560 µL/kg (Rabbit)	> 310 mg/m³(Rat)1 h

#### Information on toxicological effects

SymptomsModerately irritating to the eyes. Inhalation of high vapor concentrations may cause<br/>symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged skin<br/>contact may defat the skin and produce dermatitis.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	None known.
Germ Cell Mutagenicity	None known.
Carcinogenicity	None known.
Reproductive toxicity	None known.
Specific target organ systemic	May cause drowsiness or dizziness.

#### toxicity (single exposure)

Specific target organ systemic None known. toxicity (repeated exposure)

Aspiration hazard

None known.

# SECTION 12: ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Distillates (petroleum), hydrotreated light	1000: 72 h Pseudokirchneriella subcapitata mg/L EC50	1000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Calcium dihydroxide		160: 96 h Gambusia affinis mg/L LC50 static		
2-Methylpentane-2,4-diol	>420: 72 h Selenastrum capricornutum mg/I EC50	10500-11000: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Lepomis macrochirus mg/L LC50 static 8690: 96 h Pimephales promelas mg/L LC50 flow-through 10700: 96 h Pimephales promelas mg/L LC50 static		2700 - 3700: 48 h Daphnia magna mg/L EC50

# Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

#### **Bioaccumulation**

Chemica		log Pow		
2-Methylpent		0.14		
107-	41-5			
Other adverse effects	No information available			
	SECTION 13: DISPOSAL CONSIDERATIONS			
Waste treatment				
Waste Disposal Methods	Dispose of in accordance with federal, state, and local regulations.			
Contaminated packaging	Observe all label precautions until container is cleaned, reconditioned or destroyed.			
SECTION 14: TRANSPORT INFORMATION				
DOT UN/ID No Proper shipping name Hazard class Packing group	Not regulated in non-bulk; Combustible Liquid in bulk. NA1993 Combustible liquid, n.o.s. Combustible liquid III			

Special Provisions	IB3, T1, T4, TP1
Description	NA1993, COMBUSTIBLE LIQUID, N.O.S. (DISTILLATES (PETROLEUM),
Emergency Response Guide	HYDROTREATED LIGHT), Combustible liquid, III
Number	128
TDG	Not regulated. (If shipped in NON BULK packaging by ground transport)
UN/ID No	UN1268
Proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Hazard class	3
Packing Group	III
Description	UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III
ICAO/IATA UN No. Proper shipping name Hazard class Packing group Description	UN1268 PETROLEUM DISTILLATES, N.O.S. 3 III UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III
IMDG/IMO UN No. Proper shipping name Hazard class Packing Group EmS No. Special Provisions Description	UN1268 PETROLEUM DISTILLATES, N.O.S. 3 III F-E, S-E 223, 363, 955 UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

# **SECTION 15: REGULATORY INFORMATION**

International Inventories	
TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Complies
KECL	Complies
IECSC	Complies
ENCS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

ENCS - Japan Existing and New Chemical Substances

#### U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

## SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	Yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

## Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

#### U.S. State Regulations

#### SCAQMD Rule 1144

The sale or distribution in the SCAQM District of California for metal working fluids or direct-contact lubricants is allowed if EITHER the VOC of the product itself OR the VOC of the diluted product at the point of use is less than the following limits: (1) 75 g VOC/L for metal forming, metal removal, metal treating; (2) 50 g VOC/L for metal protection, direct-contact lubricant. The VOC of this product as sold is: ~ 402 gVOC/L (ASTM E-1868-10)

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

#### International Regulations

Mexico - Grade

Moderate risk, Grade 2

#### <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

D2B Toxic materials B3 Combustible liquid

#### Other information Not applicable

# **SECTION 16: OTHER INFORMATION**

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and chemical hazards -
STOT SE - Specific ta STOT RE - Specific ta TSCA - United States VOC - Volatile organic	previations and acronyms arget organ systemic toxicit arget organ systemic toxicit Toxic Substances Control c compounds iately Dangerous to Life or	y (Single exposure) y (repeated exposure) Act Section 8(b) Inventor		
Revision Date: Revision Note No information availat Disclaimer	08-27-20 Dle	15		
The information prov date of its publicatio		is designed only as a g	uidance for safe handli	nformation and belief at the ng, use, processing, storage, fication. The information

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.