

# Rust Veto® A-2

Fast-drying, low flash rust inhibitor

## DESCRIPTION

**Rust Veto A-2** leaves a firm, waxy, translucent film. This film is easy to apply and remove. **Rust Veto A-2** gives excellent protection to packaged items, dies and molds, precision instruments and other highly finished parts stored indoors.

This is the same rust preventive used in famous "Rust Veto Spray" aerosol applicator cans.

## FEATURES / BENEFITS

- Easily applied
- Excellent rust protection
- Over 30 days in humidity cabinet test at 100 °F; over one year indoor storage
- Easily removed by solvent or alkaline cleaners
- Film is translucent, firm, dry

## DATA (TYPICAL VALUES)

Appearance	Clear, yellow liquid
Pounds per gallon	7.25
Flash Point	80°F (26.67°C)
Film Thickness	.0003 - .0005
Solids Content	12%

## HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

EN 15.08 US



Houghton International Inc.  
 Madison and Van Buren Aves.  
 P. O. Box 930  
 Valley Forge, PA 19482-0930

Phone: 610-666-4000  
 Fax: 610-666-0174  
 info@houghtonintl.com  
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.